



## Application of laser in a optical assembly for calculation of deformations following the x and y directions

<sup>1</sup> R. Daïra; <sup>1</sup> B. Boudjema

*<sup>1</sup>Department of sciences of mater, University August 20, 1955 of skikda, Road of El Haddeik LP 26, Physico Chemistry of Surfaces and interfaces Research Laboratory of Skikda (LRPCSI), Algeria*

*E-mail : [daira\\_radouane@yahoo.fr](mailto:daira_radouane@yahoo.fr)*

The European Conference on Plasma Diagnostics is a biennial event that aims at bringing together physicists or other scientists working on diagnostics for magnetic confinement fusion, beam plasmas and inertial fusion, low-temperature and industrial plasmas, and basic and astrophysical plasmas. It is endorsed by the Plasma Physics Division of EPS [1].

We present the speckle interferometry method to determine the deformation of a piece. This method of holographic imaging using a CCD camera for simultaneous digital recording of two states object and reference. The reconstruction is obtained numerically. This latest method has the advantage of being simpler than the methods currently available, and it does not suffer the holographic configuration faults online. Furthermore, it is entirely digital and avoids heavy analysis after recording the hologram. This work was carried out in the laboratory HOLO 3 (optical metrology laboratory in Saint Louis. France) and it consists in controlling qualitatively and quantitatively the deformation of object by using a camera CCD connected to a computer equipped with software of Fringe Analysis.